

DARBY & DARBY P.C.

805 Third Avenue
New York, New York 10022
(212) 527-7700

TELECOPIER: (212) 753-6237

TELEX: 236687

COURTESY COPY

PLEASE URGENTLY DELIVER TO EXAMINER PITTS

Date: April 30, 1996

Attorney Docket No.: 2338/08419

TELECOPIER TRANSMISSION COVER SHEET

Phone Number Transmitting To: 1-703-305-3598 or
1-703-305-3597

To: **United States Patent and Trademark Office**

Examiner: Examiner Andrea L. Pitts

Group Art Unit: 3502

Paper(s) Being Transmitted: **AMENDMENT**

Number of Pages Being Transmitted (including cover): **4**

CERTIFICATION OF FACSIMILE TRANSMISSION

Serial No.: 08/135,059

Filed: 10/12/93

I hereby certify that these papers are being facsimile transferred to the United States Patent and Trademark Office on the date shown below.

Ema Gualano
Name

April 30, 1996
Date

Ema Gualano
Signature

FAX COPY RECEIVED
APR 3 1996
GROUP 3502

4/25/96
35x
Pitts

2338/08419

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of Roland SEEBACHER et al.
Serial No. 08/135,059
Filed 10/12/93
For POWER TRANSMITTING APPARATUS
 WITH FLUID COUPLING
Art Unit 3502
Primary Examiner Ms. Andrea L. Pitts

A M E N D M E N T

Hon. Commissioner of Patents
and Trademarks
Washington, D.C. 20231

FAX COPY RECEIVED
APR 2 1996
GROUP 3500

Sir:

In further response to the Official Action of December 8, 1995, and supplementary to the Paper dated April 12, 1996, please amend the above referenced patent application as follows:

In the claims:

Claim 32, line 4, change "input" to --driven--.

Amend the claim 48 as follows:

- 1 --48. (AMENDED) Power transmitting apparatus
- 2 comprising a fluid coupling including at least one housing
- 3 having an axis of rotation and connectable with a rotary
- 4 [output] driving device, at least one impeller disposed in

5 and driven by said at least one housing when said housing
6 is driven by said driving device, and at least one runner
7 disposed in said at least one housing and connectable with
8 a rotary [input] driven device; a rotary output element con-
9 nectable with said driven device; and damper means including
10 at least two torsionally elastic dampers in a power train
11 between said at least one housing and said output element,
12 each of said at least two dampers including at least one
13 energy storing element acting in a circumferential direction
14 of said at least one housing, the at least one energy storing
15 element of one of said at least two dampers being disposed
16 in a power train between said at least one runner and said
17 output element and being spaced apart from and disposed
18 radially outwardly of said axis, the at least one energy
19 storing element of the other of said at least two dampers
20 being disposed in a power train between said at least one
21 housing and said at least one runner.--.